



ERIC-A 下均质真空均质乳化机

Bottom homogenizer vacuum emulsifying mixer

下均质
Bottom homogenizer



技术参数 Technical parameter

型号 Model	物料容积 Capacity	均质马达 Homogenizer Motor		搅拌马达 Stir Motor		外形尺寸 Dimension(mm)			总功率 Total Power(KW)		极限真空 limit vacuum (Mpa)
		KW	r/min	KW	r/min	长 Length	宽 Width	高/全高 Height	蒸汽加热 Steam heating	电加热 Electric heating	
ERIC-A5	5L	0.37	0-3000	0.18	0-63	1260	540	1600/1850	2	5	-0.09
ERIC-A10	10L	0.75	0-3000	0.37	0-63	1300	580	1600/1950	3	6	-0.09
ERIC-A50	50L	3-5.5	0-3000	1.1	0-63	2600	2250	1950/2700	9	18	-0.09
ERIC-A100	100L	4-7.5	0-3000	1.5	0-63	2750	2380	2100/2950	13	32	-0.09
ERIC-A200	200L	5.5-11	0-3000	2.2	0-63	2750	2750	2350/3350	15	45	-0.09
ERIC-A300	300L	7.5-11	0-3000	2.2	0-63	2900	2850	2450/3500	18	49	-0.085
ERIC-A500	500L	11	0-3000	4	0-63	3650	3300	2850/4000	24	63	-0.08
ERIC-A1000	1000L	15	0-3000	5.5	0-63	4200	3650	3300/4800	30	90	-0.08
ERIC-A2000	2000L	15	0-3000	7.5	0-63	4850	4300	3800/5400	40	-	-0.08

注：本表中的数据因技术改进、定制而不符，以实物为准。

Note: In case of incoformity of the data in the table due to technical improvement or customization, the real object shall prevail.